

SM 55 IND-5S - Scheda tecnica



Description

SM 55 IND-5S è stato specificamente progettato per reach stacker e macchine per la movimentazione di container. La miscela speciale del battistrada, resistente all'abrasione, assicura una lunga vita dello pneumatico su superfici asfaltate o cementate, offrendo eccellente stabilità ai veicoli in modalità di sollevamento.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	PORT INDUSTRIAL	IND5	20	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	310	1275	594	3777	TT
18.00 - 25	PORT SPECIAL	IND5	40	13.00/2.5	15.00/2.5	517	1665	765	5118	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..