

## STEER GRIP - Scheda tecnica



### Description

STEER GRIP è l'equipaggiamento ideale per le assi sterzanti di autocarri con cassone ribaltabile. La larga nervatura centrale con ramponi lineari rende lo pneumatico idoneo per applicazioni free rolling, garantendo eccellenti prestazioni sia in condizioni bagnate che asciutte fuori strada. La speciale mescola del battistrada è stata realizzata per abbinare ottima resistenza all'usura e resistenza a tagli e lacerazioni, mentre la carcassa robusta assicura un ciclo di vita prolungato dello pneumatico.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

OTR: Carro con cassone ribaltabile

SIZE	Version	USACode	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	STANDARD	94047024	18	7.5	7.0	11.3	42.7	20.1	129.5	TT
11.00 - 20	STANDARD	94052103	18	8.0	7.5	11.8	44.1	20.7	133.7	TT
12.00 - 24	STANDARD	94049363	20	8.5	8.0	12.2	49.1	23.1	149	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..