

SUPER SAND - Specifiche tecniche



Description

SUPER SAND è particolarmente idoneo per rimorchi che operano su superfici sabbiose in condizioni climatiche calde. Lo pneumatico si distingue per l'elevata capacità di galleggiamento ed è ideale per tutte le operazioni che richiedono un elevato livello di manipolazione.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions International Standard

Ply Rating	12
Section Width (mm)	385
Overall Diameter (mm)	1225
Rim Rec	10.00 V
Rim Alt	10.00 W

Load capacity (Kg)

km/h / bar	2.40
65 LS	2360
65 LD	2060

Printed on 02/07/2024 18:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..