

SUPER TRAX HD - Specifiche tecniche



Description

SUPER TRAX HD è stato specificamente progettato per carrelli elevatori impiegati nella movimentazione di merci con servizio pesante, incluse le applicazioni di porto e miniera. Il battistrada extra profondo è stato realizzato con una miscela eccezionale resistente all'usura che assicura una vita operativa prolungata. SUPER TRAX HD si distingue per la carcassa robusta e il fianco rinforzato dello pneumatico che si traducono in eccellente stabilità e manovrabilità in modalità di sollevamento. Il particolare bordo di protezione del cerchio protegge lo pneumatico nell'area della balconata del cerchio da sgonfiamenti e danni.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Carrello elevatore

Version	STANDARD
Type	TT
Tyre Size	8.15 - 15 (28 X 9 - 15)

Dimensions US Standard

Usa code	94056552
Ply Rating	14
Section Width (inch)	8.7
Overall Diameter (inch)	28.1
Static Loaded Radius (inch)	13.1
Rolling Circumference (inch)	85.4
Rim Rec	7.00
Rim Alt	7 BD

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	8600
15 STEER WHEEL	6615
5 OTHER VEHICLES	8600
15 OTHER VEHICLES	6615
STATIC SIDE LOADER	9985

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..