

SURE TRAX HD - Specifiche tecniche



Description

SURE TRAX HD è uno pneumatico con disegno del battistrada a blocchi per pale **skid steer** per applicazioni nel settore costruzioni. Lo pneumatico mostra eccellente resistenza a tagli e strappi oltre alla massima protezione del cerchio. SURE TRAX HD è ideale per superfici pavimentate e operazioni di servizio pesante.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions US Standard

Usa code	94017966
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	91.2
Rim Rec	8.25

ECE

Load capacity (lbs)

mph / psi	75
5	4710
10	3710
15	3440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..