

TF 8181 - Specifiche tecniche



Description

TF 8181 è uno pneumatico per l'impiego su campo e su strada sviluppato per trattori 2WD/2RM nelle applicazioni di lavorazione del terreno e di trasporto. Questo pneumatico assicura elevate prestazioni di sterzata.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore 2WD

Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	94 A8

Dimensions US Standard

Usa code	94020645
Ply Rating	6
Section Width (inch)	8.1
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	15.1
Rolling Circumference (inch)	96.3
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
ECE	E4-106R-002634
TRA Code	F2

Load capacity (lbs)

mph / psi	44
25	1480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..