

TF 9090 - Specifiche tecniche



Description

TF 9090 è uno pneumatico progettato per trattorini nelle operazioni di lavorazione della terra. Il particolare disegno del battistrada garantisce un ottimo controllo di sterzata su terreno sciolto.

UM

International Standard

Construction

BIAS

Machinery

Agricoltura: Trattorino
Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	91 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	180
Overall Diameter (mm)	765
Static Loaded Radius (mm)	359
Rolling Circumference (mm)	2280
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F ; 5.50 F
ECE	E4-106R-001960
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.10
30	615

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 05:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..