

## TF 9393 - Scheda tecnica



### Description

TF 9393 è uno pneumatico frontale agricoltura particolarmente sviluppato per trattorini per la lavorazione del suolo ed è particolarmente idoneo per terreni sciolti. Il battistrada è caratterizzato da una larga parte centrale e da costole nell'area della spalla. Il particolare disegno del battistrada assicura ottima sterzata su tutte le superfici.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattorino

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 6.00 F	210	810	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..