

TR 126 - Scheda tecnica



Description

TR 126 è stato sviluppato per trattorini nelle operazioni di lavorazione della terra. I ramponi profondi e il particolare disegno del battistrada offrono eccellente trazione e straordinaria capacità di carico che si traducono in elevatissime prestazioni in tutte le condizioni operative.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattorino

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
6 - 14	HD	94069972	R1	77 A8	8	5 JA ; 5 KB		6.2	25.8	12	77.9	TT	E11-106R-007418
6 - 14	STANDARD	94053513	R1	63 A8	4	5 JA ; 5 KB		6.2	25.8	12	77.9	TL	E11-106R-003476
6 - 14	STANDARD	94004522	R1	63 A8	4	5 JA ; 5 KB		6.2	25.8	12	77.9	TT	E11-106R-003476
7 - 14	STANDARD	94052639	R1	92 A8	8	5 JA ; 5 KB		6.7	27.2	12.6	81.5	TT	E11-106R-005233
7 - 14	STANDARD	94053520	R1	68 A8	4	5 JA ; 5 KB		6.7	27.2	12.6	81.5	TL	E11-106R-003356
7 - 14	STANDARD	94004539	R1	68 A8	4	5 JA ; 5 KB		6.7	27.2	12.6	81.5	TT	E11-106R-003356

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..