

TR 137 - Specifiche tecniche



Description

TR 137 è lo pneumatico più idoneo di BKT per tutte le operazioni di raccolto, assicurando un'eccellente trazione sul campo anche con carichi elevati. Lo pneumatico è disponibile in diverse versioni: la versione "aramid-belted", con cinture in aramide, garantisce migliore resistenza alla perforazione e protezione contro tutti i danni tipici di questa applicazione; la versione "HD" offre una straordinaria resistenza a tagli e lacerazioni nonché un ciclo di vita prolungato.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia

Version	STANDARD
Type	TL
Tyre Size	30.5L - 32
LI/SS	164 A6

Dimensions International Standard

Ply Rating	14
Section Width (mm)	770
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	831
Rolling Circumference (mm)	5520
Rim Rec	DH 27 B
Rim Alt	DW 27 B
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.60
30	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..