

## TR 137 - Specifiche tecniche



### Description

TR 137 è lo pneumatico più idoneo di BKT per tutte le operazioni di raccolto, assicurando un'eccellente trazione sul campo anche con carichi elevati. Lo pneumatico è disponibile in diverse versioni: la versione "aramid-belted", con cinture in aramide, garantisce migliore resistenza alla perforazione e protezione contro tutti i danni tipici di questa applicazione; la versione "HD" offre una straordinaria resistenza a tagli e lacerazioni nonché un ciclo di vita prolungato.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agricoltura: Mietitrebbia

Version	HD
Type	TL
Tyre Size	30.5L - 32
LI/SS	167 A8

## Dimensions US Standard

Usa code	94004355
Ply Rating	18
Section Width (inch)	30.3
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	32.7
Rolling Circumference (inch)	217.3
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E4-106R-002283
TRA Code	R1

## Load capacity (lbs)

mph / psi	30
25	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..