

TR 315 - Specifiche tecniche



Description

TR 315 è uno pneumatico idoneo per tappeti erbosi e giardinaggio in ambito municipalità e nelle operazioni di lavorazione della terra. Lo pneumatico è ideale per l'impiego con attrezzi agricoli, scavafossi e macchine per il raccolto di frutteti. TR 315 mostra un'ampia area di contatto che fornisce eccellente grip, straordinarie qualità di autopulitura nonché eccellente stabilità in qualsiasi condizione.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Macchina per il raccolto di frutteti • Scavafossi

Version	STANDARD
Type	TL
Tyre Size	26 X 12.00 - 12

Dimensions International Standard

Ply Rating	4
Section Width (mm)	308
Overall Diameter (mm)	655
Static Loaded Radius (mm)	289
Rolling Circumference (mm)	1905
Rim Rec	10½ JA
Rim Alt	8½ JA ; 9½ JA
ECE	E11-106R-003494

Load capacity (Kg)

km/h / bar	1.40
15	800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..