

TR 318 - Specifiche tecniche



Description

TR 318 è stato particolarmente progettato per irroratrici e attrezzi agricoli. I ramponi a doppia angolazione assicurano una trazione eccellente e un comfort di guida straordinario. TR 318 offre inoltre ottime qualità di autopulitura. La robusta carcassa garantisce la massima durabilità.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Macchina irroratrice

Version	STANDARD
Type	TL
Tyre Size	23 X 9.00 - 12
LI/SS	93 A3

Dimensions International Standard

Ply Rating	6
Section Width (mm)	220
Overall Diameter (mm)	585
Rim Rec	7.0
ECE	E11-106R-004521

Load capacity (Kg)

km/h / bar	3.0
15	650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..