

## TR 360 - Specifiche tecniche



### Description

TR 360 è idoneo per attrezzi agricoli nelle applicazioni di trasporto su e fuori strada nonché per prati e giardinaggio. Il particolare disegno del battistrada, insieme alla struttura della carcassa, garantiscono un ciclo di vita lungo dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TL
Tyre Size	240/70 - 15 (28X9.00 - 15)
LI/SS DRIVE WHEEL	115 A8

## Dimensions US Standard

Usa code	94075416
Ply Rating	8
Section Width (inch)	9.3
Overall Diameter (inch)	29.1
Rim Rec	7.00 I
Rim Alt	6 ½ K
ECE	E11-106R-008778

## Load capacity (lbs)

mph / psi	58
10	2680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 05:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..