

TR 360 - Scheda tecnica



Description

TR 360 è idoneo per attrezzi agricoli nelle applicazioni di trasporto su e fuori strada nonché per prati e giardinaggio. Il particolare disegno del battistrada, insieme alla struttura della carcassa, garantiscono un ciclo di vita lungo dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli

SIZE	Version	LI/SS DRIVE WHEEL	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 7 - 8	STANDARD		6	5.5		180	460	202	1334	TL	E4-106R-002184
240/70 - 15 (28X9.00 - 15)	STANDARD	115 A8	8	7.00 I	6 ½ K	235	740	0	0	TL	E11-106R-008778

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 05:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..