

TR 387 - Specifiche tecniche



Description

TR 387 è uno pneumatico agro-industriale, idoneo per rimorchi per la canna da zucchero e compattatori. Lo pneumatico si distingue per l'elevata capacità di carico ed è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche degli utilizzatori in termini di resistenza a tagli e lacerazioni, operazioni di servizio pesante e durabilità. La versione "dual bead", a doppio tallone, è particolarmente idonea per trattori industriali e operazioni di trasporto con rimorchi.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Industriale: Compattatore

Version	STANDARD
Type	TL
Tyre Size	23.1 - 26
LI/SS	141 A8

Dimensions US Standard

Usa code	94005048
Ply Rating	8
Section Width (inch)	23.3
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	184.6
Rim Rec	DW 20 B
ECE	E11-106R-003595
TRA Code	R3

Load capacity (lbs)

mph / psi	16
25	5680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 02:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..