

## TR 678 - Specifiche tecniche



### Description

TR 678 è stato particolarmente sviluppato per applicazioni forestali. Il robusto disegno dei tasselli garantisce trazione e autopulitura eccellenti. La tenace struttura della carcassa si traduce in elevata capacità di carico, mentre le cinture in acciaio proteggono lo pneumatico da forature e danni. TR 678 è caratterizzato da una mescola resistente ai tagli che garantisce, anche su terreni difficili in condizioni estreme, eccellente resistenza a tagli e lacerazioni.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Rimorchio  
Industriale: Escavatore • Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	600/55 - 26.5
LI/SS	172 A2 / 165 A8

## Dimensions US Standard

Usa code	94074112
Ply Rating	20
Section Width (inch)	23.8
Overall Diameter (inch)	53.1
Rim Rec	AG 20.00
ECE	E11-106R-008132
TRA Code	LS2

## Load capacity (lbs)

mph / psi	80
25	11355
5	13890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 16:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..