

## TR 678 - Specifiche tecniche



### Description

TR 678 è stato particolarmente sviluppato per applicazioni forestali. Il robusto disegno dei tasselli garantisce trazione e autopulitura eccellenti. La tenace struttura della carcassa si traduce in elevata capacità di carico, mentre le cinture in acciaio proteggono lo pneumatico da forature e danni. TR 678 è caratterizzato da una miscela resistente ai tagli che garantisce, anche su terreni difficili in condizioni estreme, eccellente resistenza a tagli e lacerazioni.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Rimorchio  
Industriale: Escavatore • Rimorchio

|           |                 |
|-----------|-----------------|
| Version   | STEEL BELTED    |
| Type      | TL              |
| Tyre Size | 600/65 - 34     |
| LI/SS     | 166 A2 / 162 A6 |

## Dimensions US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94043378 |
| Ply Rating                   | 16       |
| Section Width (inch)         | 24       |
| Overall Diameter (inch)      | 64.7     |
| Static Loaded Radius (inch)  | 29.8     |
| Rolling Circumference (inch) | 193.5    |
| Rim Rec                      | DW 20 B  |
| TRA Code                     | LS2      |

## Load capacity (lbs)

| mph / psi | 38.0  |
|-----------|-------|
| 20        | 10470 |
| 5         | 11685 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 16:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..