

## TUF LUG - Scheda tecnica



### Description

TUF LUG è idoneo per rimorchi e autocarri leggeri nelle applicazioni di trasporto. Lo pneumatico offre ottima trazione e straordinaria durabilità, assicurando un lungo ciclo di vita del prodotto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Autocarro leggero • Rimorchio  
Industriale: Autocarro leggero • Rimorchio

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
7.50 - 16	STANDARD	12	6.00 G	5.50 F	216	830	TT
7.50 - 16	STANDARD	14	6.00 G	5.50 F	216	830	TT
7.50 - 16	STANDARD	16	6.00 G	5.50 F	216	830	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..