

XL GRIP (ADT) - Scheda tecnica



Description

XL GRIP (ADT) è un pneumatico a tele diagonali per dumper articolati progettato per ridurre al minimo tagli e forature in condizioni difficili, in cui è richiesta una trazione eccezionale. Queste caratteristiche si traducono in una maggiore durata dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper articolato

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 - 25	STANDARD	E3	32	22.00/3.0		680	1740	796	5150	TL
26.5 - 25	STANDARD	E3	28	22.00/3.0		680	1740	796	5150	TL
29.5 - 25	STANDARD	E3	28	25.00/3.5		760	1860	849	5544	TL
29.5 - 25	STANDARD	E3	32	25.00/3.5		760	1860	849	5544	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..