

## XL GRIP (BHL) - Specifiche tecniche



### Description

XL GRIP (BHL) è stato particolarmente sviluppato per terne che vengono impiegate in operazioni pesanti nelle applicazioni di scavo, spianamento e carico. Il disegno non direzionale del battistrada assicura ottima trazione e stabilità. La speciale mescola del battistrada si traduce in eccellente resistenza a tagli e lacerazioni e prolunga la vita del battistrada.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Terna

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 20

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Overall Width (mm)</b>	320
<b>Overall Diameter (mm)</b>	1155
<b>Static Loaded Radius (mm)</b>	545
<b>Rolling Circumference (mm)</b>	3465
<b>Rim Rec</b>	8.5
<b>Rim Alt</b>	8.0

## Load capacity (Kg)

km/h / bar	8.60	7.90
10	5680	-
40	-	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/03/2025 02:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..