

XL GRIP (L3) - Specifiche tecniche



Description

XL GRIP (E-3/L-3) è uno pneumatico a tele incrociate di base larga (wide) sviluppato per loader al fine di minimizzare il rischio di tagli e perforazioni nelle applicazioni pesanti di carico. Lo pneumatico assicura eccellente trazione insieme ad un ciclo di vita prolungato del prodotto.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Pala caricatrice

OTR: Dozer • Pala caricatrice

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions US Standard

Usa code	94015856
Ply Rating	20
Overall Width (inch)	20.9
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	173
Rim Rec	17.00/2.0
TRA Code	E3/L3
Tread Depth	41

Load capacity (lbs)

mph / psi	47	65
30	13200	-
5	-	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/03/2025 03:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..