

XL GRIP PLUS - Specifiche tecniche



Description

XL GRIP PLUS (L-4) è stato specificamente sviluppato per loader. Il battistrada profondo assicura ottima resistenza a tagli e forature oltre ad un ciclo di vita prolungato dello pneumatico. XL GRIP PLUS è particolarmente idoneo per operazioni di servizio pesanti.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dozer • Pala caricatrice

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions US Standard

Usa code	94059577
Ply Rating	36
Overall Width (inch)	29.9
Overall Diameter (inch)	75.4
Static Loaded Radius (inch)	34.5
Rolling Circumference (inch)	224.8
Rim Rec	25.00/3.5
TRA Code	L4

Load capacity (lbs)

mph / psi	83
5	46100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 09:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..